Amendments to the Claims:

This listing of claim will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A heat exchanger exchanging device comprising;

an evaporator having a first predetermined portion and a predetermined second portion;

a blower;

an air inlet unit; and

an air outlet unit,

wherein air is fed from outside into the inner-part of the heat exchanger through the air inlet unit and then the air flows towards the blower through a first predetermined portion of the evaporator to thereby supply first heat-exchanged air and thereafter, the first heat-exchanged air is fed to the air outlet unit through a second predetermined portion of the evaporator by the blowing operation of the blower to thereby supply second heat exchanged air

wherein the first predetermined portion of the evaporator is disposed between the air inlet and the blower and the second predetermined portion of the evaporator is disposed between the blower and the air outlet.

Claim 2 (canceled)

Claim 3 (canceled)

Yong-Kyu KWON, *et al.* 09/931.423

Claim 4 (currently amended): The heat exchanger exchanging device according to elaim 3 claim 1, wherein the first predetermined portion and the second predetermined portion are a center portion and an end portion of the evaporator, respectively.

Claim 5 (withdrawn): The heat exchanger according to claim 3, wherein the first predetermined portion and the second predetermined portion are an end portion and a center portion of the evaporator, respectively.

Claim 6 (currently amended) The heat exchanger exchanging device according to claim 1, further comprising a guide unit for guiding flow of the first heat-exchanged air.

Garx Dy

Claim 7 (currently amended): A heat exchanger exchanging device comprising:

an evaporator having a first predetermined portion and a second predetermined portion;

at least one blower;

at least one air inlet; and

at least one air outlet,

wherein the first predetermined portion of the evaporator is disposed between the at least one air inlet and the blower and the second predetermined portion of the evaporator is disposed between the blower and the at least one air outlet.

Claim 8 (canceled)

Claim 9 (canceled)

Claim 10 (currently amended): The heat exchanger exchanging device according to claim 7, wherein the first predetermined portion and the second predetermined portion are a center portion and an end portion of the evaporator, respectively.

Claim 11 (withdrawn): The heat exchanger according to claim 7, wherein the first predetermined portion and the second predetermined portion are a center portion and an end portion of the evaporator, respectively.

Claim 12 (currently amended): The heat exchanger exchanging device according to claim 7, further comprising a guide unit for directing air flow from the at least one air inlet through the first predetermined portion of the evaporator to the blower.

The heat exchanger exchanging device according to Claim 13 (currently amended): claim 7, further comprising a guide unit for directing air flow from the blower through the second predetermined portion of the evaporator to the at least one air outlet.

Claim 14 (currently amended): A method of conditioning air comprising the steps of:

(a) providing the heat exchanger exchanging device of claim 7 comprising: an evaporator having a first predetermined portion and a second predetermined portion; at least one blower;

at least one air inlet; and

at least one air outlet,

wherein the first predetermined portion of the evaporator is disposed between the at least one air inlet and the blower and the second predetermined portion of the evaporator is disposed between the blower and the at least one air outlet;



- (b) providing unconditioned air into the at least one air inlet;
- (c) feeding at least a portion of the unconditioned air through [[a]] the first predetermined portion of the evaporator towards the blower;
- (d) directing at least a portion of the first heat-exchanged air form the blower through

 [[a]] the second predetermined portion of the evaporator.